



CAST Craftsman Series Borneo Path Light (CCPLBOB and CCPLBOBL)

Now Available with Integrated LED or Drop-In LED!



Description:

These solid bronze path lights are compact with extreme durability. Now available with integrated LED lamps or bi-pin drop-in LED lamps.

Features:

Durability

- ▶ CAST solid sand-cast bronze for unmatched corrosion resistance
- ▶ Unbreakable bodies, hats, stems, and stake
- ▶ No coatings to peel, flake, chip, or fade
- ▶ No threads that weaken stems
- ▶ Marine-grade Tin-Coated No-Ox Wire for lifetime electrical conductivity.

Performance

- ▶ Premium-quality LEDs deliver consistent color temperature and accurate color rendering.
- ▶ Electronics protected from electrical spikes and surges.
- ▶ Electromagnetic radiation (EMI) filtered to prevent interference with wireless devices

Uses:

Suitable for lighting walkways, planting beds, and other areas.

Dimensions:

8.5" stake, 19" height body and stem

Square Hat: 6" x 6" x 2" height


Specifications:

CCPL2B Integrated LED:

- LED components integrated into fixture bodies to draw heat away from the LEDs for maximum longevity and performance.
- Fully sealed and protected LED components.
- LED Light Source: 2 Cree LED, Life (L70): 62,000 Hrs.
- Color Temp: 2790°K, CRI: 82
- Input Voltage: 10-24 Volts AC or DC
- Power: .4 Amps, 4.22 Watts, Power Factor .89, Volt Amps 4.74
- Lumen output-fixture: 114 lm
- Maximum Candela: 46

CCPL2BL Drop-In LED:

- Lamp is field replaceable.
- LED Light Source: SLBP250L Drop-In Bi-Pin Lamp (included).
- Color Temp: 2750°K, CRI: 80
- Voltage Range: 10-20 Volts AC or DC
- Power: 2.5 Watts, Volt Amps 3.0
- Lumen output-fixture: 114 lm



Construction:

Solid sand cast Bronze hat and stake; copper stem; 5' tin-coated #18-2 No-Ox® marine-grade wire.

Listing:

U.L 1838 Listed Low Voltage Luminaire for wet locations.