

SSPK12



INTEGRATED LED 12.5 WATT SPOT LIGHT

PRODUCT SPECIFICATIONS



Fixture Material	Die-cast aluminium
Fixture Finish	Powder-coated bronze
Glass	Clear glass
Optic	High temperature Japanese acrylic
Cowl Material	Die-cast aluminium
LED Chip	Nichia
Binning	3 step MacAdam
Wiring	3.25' of 2 core 0.75mm rubber cable
Lifespan	50,000 hours
Color Rendering Index	>85
Input Voltage	12VAC, 50/60Hz or 12VDC
Operating Temperature	from -4° to 149°F
Warranty	3 years against manufacturing defects

Standard offering of fixture is 3000K and 35° Beam Spread. Other color temperatures (2700K, 4000K & 6000K), colors (red, green, blue) and beam spreads (10° and 65°) are available as a special order. Special orders require a minimum of 100 units and lead times for special orders are 8 weeks. Special orders require a 50% deposit on materials and any expedited freight charges will be the responsibility of the client.



Power (W)	Available Color Temperatures	Luminous Flux			IP Rating	Available Beam Angles
		3000K	4000K	6000K		
12.5 W	2700K 3000K 4000K 6000K RED GREEN BLUE	110lm/W	120lm/W	130lm/W	66	10° 35° 60°